

Ordering Information

STEP 1 Connector Type	STEP 2 Polish Finish (Ref. Step1)	STEP 3 Connector Type	STEP 4 Polish Finish (Ref. Step3)	STEP 5 Fiber Mode	STEP 6 Cable Length in Meters	STEP 7 Cable Diameter	STEP 8 Core/ Cladding Diameter	STEP 9 Boot	STEP 10 RoHS Compliant per EC Directive	STEP 11 Special Options
-----------------------------	---	-----------------------------	---	----------------------	-------------------------------------	-----------------------------	---	----------------	--	-------------------------------

Step	1	2	3	4	5	6	7	8	9	10	11
Example	1	B	2	B	S	3.0	F	4	9	AA	

STEP 1 - Connector Type

- 1 - FC
- 2 - SC
- 3 - LC

STEP 2 - Polish Finish (Ref. Step1)

- A - PC (Physical Contact)
- B - UPC (Ultra Physical Contact)
- C - APC (Angle Physical Contact)
- D - SPC (Super Physical Contact)

STEP 3 - Connector Type

- 1 - FC
- 2 - SC
- 3 - LC

STEP 4 - Polish Finish (Ref. Step3)

- A - PC (Physical Contact)
- B - UPC (Ultra Physical Contact)
- C - APC (Angle Physical Contact)
- D - SPC (Super Physical Contact)

STEP 5 - Fiber Mode

- S-Single Mode
- M-Multimode

STEP 11 - Special Options

Consult Factory

STEP 10 - RoHS Compliant per EC Directive 2002/95/EC

- 0= Non AA
- AA = Compliant

STEP 9 - Boot

- 0 - No boot
- 8 - Rubber boot
- 9 - Bellcore boot

STEP 8 - Core/Cladding Diameter

- 4 - Single Mode 9/125
- 5 - Multi Mode 50/125
- 6 - Multi Mode 62.5/125

STEP 7 - Cable Diameter

- E - 2MM Jacketed Cable
- F - 2.4MM Jacketed Cable
- G - 3MM Jacketed Cable
- H - 900UM Buffer Cable

STEP 6 - Cable Length in Meters XX.X (1.0m - 99.9m)

Examples of typical cable lengths - ref. only

1.0M	5.0M
2.0M	10.0M
2.5M	15.0M
3.0M	

STEP 6 Note:

* Cable Length Tolerance

Length tolerance :

Less than 1 meter:

- +0.05/-0.0 meter

Equal or Longer than 1 meter but less than 5 meter :

- +0.25/-0.0 meter.

Equal or Longer than 5 meter:

- +0.5/-0.0 meter.

Consult factory for ST, MU, DIN, MTRJ Applications
Consult factory for adapters