



ORDERING INFORMATION - CODE NUMBERING SYSTEM


Specify Complete Connector By Selecting An Option From Step 1 Through 7

STEP	1	2	3	4	5	6	7	8	9
EXAMPLE	PLS	5W5	M	4	0	0	A1	/AA	
STEP 1 - BASIC SERIES	<p>PLS - PLS Series PLSH - High conductivity contacts</p>								<p>STEP 9 - SPECIAL OPTIONS</p> <p>CONTACT TECHNICAL SALES FOR SPECIAL OPTIONS</p>
STEP 2 - CONNECTOR VARIANTS	<p>5W5 - Five size 12 contacts 7W7 - Seven size 12 contacts</p>							<p>STEP 8 - ENVIRONMENTAL COMPLIANCE OPTIONS</p> <p>/AA - Compliant per EU Directive 2002/95/EC (RoHS)</p> <p>NOTE: If compliance to environmental legislation is not required, this step will not be used. Example: PLS5W5M400A1</p>	
STEP 3 - CONNECTOR GENDER	<p>M - Male F - Female</p>								<p>STEP 7 - CONTACT PLATING FOR PRINTED BOARD CONNECTORS</p> <p>0 - Crimp Contacts ordered separately, see pages 47-53. A1 - Gold flash over nickel on mating end and termination end. A2 - Gold flash over nickel on mating end and 0.00020 inch [5.00µ] tin-lead solder coat on termination end. C1 - 0.000030 inch [0.76µ] gold over nickel on mating end and termination end. C2 - 0.000030 inch [0.76µ] gold over nickel on mating end and 0.00020 inch [5.00µ] tin-lead solder coated termination end. D1 - 0.000050 inch [1.27µ] gold over nickel on mating end and termination end. D2 - 0.000050 inch [1.27µ] gold over nickel on mating end and 0.00020 inch [5.00µ] tin-lead solder coated termination end.</p>
STEP 4 - CONTACT TERMINATION TYPE	<p>0 - Order contacts separately for cable connectors for connection systems 5, 6, 7 and 8, see pages 47-53. Female connectors only. ** 1 - Order contacts separately for Panel Mount connectors for connection system 7, see pages 47-53. For 7W7 female variant consult technical sales. 3 - Solder, Straight Printed Board Mount with 0.146 [3.71] tail extension for connection system 6. Male connectors only. *** 4 - Solder, Right Angle (90°) Printed Board Mount with 0.146 [3.71] tail extension for connection system 5. Male connectors only. ***</p>							<p>STEP 6 - CABLE ADAPTER</p> <p>0 - None 5 - Top Opening Hood, see accessories section page 64.</p>	
STEP 5 - MOUNTING STYLE	<p>0 - None. N - Push-on Fastener for Straight Printed Board Mount Connectors</p>								




SAFETY SHROUD

NOTE: Once you have made a connector selection, contact Technical Sales if you would like to receive a drawing in DXF, PDF format or a 3-dimensional IGES file.



SK Drawing



3-dimensional model

** Consult technical sales for availability of male version of contact type 0.

*** Consult technical sales for availability of female version of contact type 3 and 4.

Connector Excellence
POSITRONIC INDUSTRIES

Connector Families

Power

D-SUBMINIATURE
Circular

RECTANGULAR

Hermetic

HERMOCOUPLER



POSITRONIC INDUSTRIES, INC.

423 N Campbell Ave • PO Box 8247 • Springfield, MO 65801
Tel (417) 866-2322 • Fax (417) 866-4115 • Toll Free (800) 641-4054
info@connectpositronic.com • www.connectpositronic.com