




SK7417


POSITRONIC INDUSTRIES BELIEVES THE DATA ON THIS DRAWING TO BE RELIABLE. SINCE THE TECHNICAL INFORMATION IS GIVEN FREE OF CHARGE, THE USER EMPLOYS SUCH INFORMATION AT HIS OWN DISCRETION AND RISK. POSITRONIC INDUSTRIES ASSUMES NO RESPONSIBILITY FOR RESULTS OBTAINED OR DAMAGES INCURRED FROM USE OF SUCH INFORMATION IN WHOLE OR IN PART.

DATE	REV	REVISION RECORD	APP	DR	CK
5-16-06	NC	ECO 25969		COLE	



NOTES:

- MATERIALS AND FINISHES:  
INSULATOR - GLASS FILLED POLYESTER, UL 94V-0, COLOR BLUE.
- ELECTRICAL CHARACTERISTICS:  
INSULATOR RESISTANCE - 5 G OHMS PER IEC 512-2, TEST 3a, METHOD A.  
WORKING VOLTAGE - 300 VAC.
- TEMPERATURE RANGE -55°C TO +125°C.
- DIMENSIONS ARE IN INCHES [MILLIMETERS].

 <b>POSITRONIC INDUSTRIES INC.</b> www.connectpositronic.com		SCALE		DRAWN BY	
 DECIMAL TOL. $\pm 0.015 [0.38]$		N.T.S.		COLE	
 ANGULAR TOL. $\pm 5^\circ$		TITLE <b>PLB10W2M0000</b>		APPROVED BY	
DATE		DRAWING NUMBER		REV.	
5-16-06		SK7417		NC	