

ORDERING INFORMATION – CODE NUMBERING SYSTEM

**Specify Complete Connector By Following Steps 1 Through 9
Insert “0” When Step Is Not Used**

Upper Connector

STEP 1 - Basic Series

CBDPB Series
CBDPC Series

STEP 2 - CBDP Series Connector Variants

Shell Size 1
5W1

Shell Size 2
3W3, 3WK3, 7W2, 11W1

Shell Size 3
5W5, 9W4, 13W3, 17W2, 21W1

Shell Size 4
8W8, 13W6, 17W5, 21WA4, 25W3, 27W2

STEP 3 - Connector Gender

M – Male
F – Female

**STEP 4 - Locking, Polarizing, Mounting and Push-on
Fastener Systems**

0 – None
R2 – Bracket, Mounting, 90° Metal, Swaged to Connector with
4-40 Thread, Fixed Female Jackscrews and Cross Bar
R6 – Bracket, Mounting, 90° Metal, Swaged to Connector with
0.120 [3.05] Ø Mounting Hole with Cross Bar
R7 – Bracket, Mounting, 90° Metal, Swaged to Connector with
4-40 Threads with Cross Bar
R8 – Bracket, Mounting, 90° Metal, Swaged to Connector with
4-40 Locknut with Cross Bar
N2 – Bracket, Mounting, 90° Metal, Swaged to Connector with
4-40 Thread, Fixed Female Jackscrews with Cross Bar
and Push-On Fastener
N6 – Bracket, Mounting, 90° Metal, Swaged to Connector with
4-40 Threads with Cross Bar and Push-on Fastener
N7 – Bracket, Mounting, 90° Metal, Swaged to Connector with
4-40 Threads with Cross Bar and Push-on Fastener
N8 – Bracket, Mounting, 90° Metal, Swaged to Connector with
4-40 Locknut with Cross Bar and Push-on Fastener
T – Fixed Female Jackscrews
T2 – Fixed Female Jackscrews
T6 – Fixed Male and Female Polarized Jackscrews

5	6	7
7W2	M	R7T

Options are
the same as
for Upper
Connector
Steps 2, 3,
and 4

8
0

STEP 8 - Shell Options

0 – Zinc Plated with Dichromate Seal
X – Tin Plated
Z – Tin Plated and Dimpled - male
connector only

9

Lower Connector

STEP 9 - Special Options

Consult Sales Department

Note: Size 8 removable power contacts with solder or
crimp terminations with power ratings of 10, 20 and
40 amperes may be ordered in lieu of the 90°
board mounted power contact. Removable size 8
shielded and high voltage contacts may also be
ordered separately in lieu of the power contact.
See catalog of Combo-D Subminiature-D
Connectors for contact part numbers.

